

HLP-1A600-EU Portable Power Station

Haier



Small but powerful, bidirectional charging and discharging



Rapid charge and discharge

Fully charged within 1.5 hours, 80% charge within 1 hour



High quality cells

LFP cell, >3500 life cycles



Smart APP

Complete smart connection for flexible control




Display

Big screen



UPS

Back-up switch time < 10ms

Model	HLP-1A600-EU
Picture	
Cell type	LFP
Nominal energy	448 Wh
AC output	
AC output	600 W (1200 W peak)
Continuous output power	220 V / 50 Hz (pure sine wave)
DC output	
USB A output	QC 3.0, 18 W
USB C output	PD 3.0, 100 W; 2 ports max 130 W
Wireless	15 W
DC 5521	12.5 V / 5 A
Cigarette lighter socket	12.5 V / 10 A
AC / CIG / PV input	
PV input	11 V - 26 V, 100 W
Cigarette lighter socket	11 V - 26 V / 8 A, 100 W
AC input	220 V, 450 W (Around 1.5 hours fully charge)
General data	
Life cycle	> 3500 times
Headlight	2 W LED light
Back light	3 W LED light
Pass-through charging	Support
Total input ports	2
Total output ports	10
UPS	< 10 ms
Temperature	Charing: 0 ~ +45 °C
	Discharging: -10 ~ 45 °C
	Storage: -10 ~ 45 °C
Net weight	7.45 kg
Dimension	295 * 252 * 219
Certifications	CE-EMC/CE-LVD, ROHS, UN38.3

*All rights reserved. Subject to change without notice.